

# Multimode OM4 Indoor Tight Buffer Single Tube, LSZH - FFLM4STx



## DESCRIPTION

FABNET fiber optic cable is designed for installation in riser and horizontal environments and inter building backbone structures. Fiber standards consists of 04 to 24 strands of fiber with 900µ tight or semi-tight buffer tube, protected aramid yarn layer is for strength and physical support. Outer jacket made of low smoke zero halogen materials that use in applications where smoke emission and toxic fumes could pose a risk to human health and essential equipment in the event of a fire. (LSZH)

## APPLICATIONS

- Operates at wavelengths of 850 nm and 1300 nm.
- ETHERNET: 10BASE - 10GBASE(100BASE, 1000BASE, 10GBASE).
- Metal free indoor cable
- High flexibility and light weight
- Halogen free and non-corrosive fire gases
- Cables are specifically designed for indoor applications, mainly used in intra-building

## SPECIFICATIONS & FEATURES

- Compliant with ANSI/TIA-568.3-D, ISO/IEC 11801
- Outer Jacket: LSZH (Low Smoke Zero Halogen) flame retardant, Violet/Black
- 900 Microns Tight buffered fibers support fast field installations.
- High Modulus, Aramid yarn as a peripheral strength member.

## MECHANICAL & PHYSICAL PROPERTIES

<b>Number of cores</b>	04 to 24 Cores	<b>Fiber Type</b>	OM4 Multimode (G.651)
<b>Impact</b>	Wp=1J, R:12.5cm, 3 impacts	<b>Tensile Force</b>	200 N (Installation)
<b>Tensile Force</b>	100 N (In Service)	<b>Crush Resistance</b>	1000 N (Installation)
<b>Flame Test</b>	IEC 60332-1-2	<b>Cable Bending</b>	R= 20 x D, 6 turns, 10 cycles
<b>Color of Fibers in Per Tube (12 Core)</b>	Blue,Orange,Green,Brown,Slate,White,Red,Black,Yellow,Violet, Rose, Aqua	<b>Operating Temperature</b>	-20 to +60 °C
<b>Flammability Rating</b>	EuroClass/LSZH	<b>Installation Temperature</b>	-5 to +50 °C
<b>Jacket Color</b>	Violet/Black	<b>Storage Temperature</b>	-40 to +70 °C
<b>Flame Test</b>	IEC 60332-1-2	<b>Repeated Bending</b>	R= 20 x D, 25 cycles, 40 N

## TRANSMISSION CHARACTERISTICS & RATINGS

Attenuation at 850 nm (dB/Km)	≤ 2.5
Attenuation at 1300 nm (dB/Km)	≤ 0.8
Fire Propagation	IEC 60332-1-2
Smoke Density	IEC 61034-2
Halogen Acid Gas	IEC 60754-1
Degree of Acidity	IEC 60754-2
2011/65/EC (RoHS)	Compliant

## PACKING DETAILS

Length (Mtr)	Approx. OD(mm)	Packaging Type
1000	6.8±0.3	DRUM
2000	6.8±0.3	DRUM

## ORDERING INFORMATION

FFLM4STx	Multimode OM Indoor Tight Buffer Single tube LSZH Bulk Cable, Violet
x-Fiber Core Variants (04/06/08/12/24)	