

Voice Patch Panel, Cat3, 50 Port, 1RU, Straight, Black- FVPP3U50F



DESCRIPTION

FABNET UTP voice category 3 patch panels are 19-inch rack-mountable IDC/PCB molded jack patch panels and are available in 25/50 port density. All panels comply with the EIA/TIA Standard for category 3, including ANSI/TIA-568-C.2 Every patch panel is made with high-quality materials, tested and certified by UL and RoHS compliant.

APPLICATIONS

- Standard 19" rack compatible.
- Height: 1U (50 ports).
- Telecommunications/Voice applications

SPECIFICATIONS & FEATURES

- Compliant with ANSI/TIA-568.2-C, ISO/IEC 11801 Category 3
- High quality metal frame. Robust and easy-to-install design.
- Cable assembly via color-coded LSA strips according to EIA/TIA 568 A&B
- Organizer for patch panel backside provides simple and easy termination and cable arrangement
- Suitable for 483 mm (19") cab mounting
- ROHS compliance: Compliant

PHYSICAL PROPERTIES

Panel type	Flat	Category	Category 3
Panel Width	482.60 mm (19")	Panel Height	1U
Outlet style	RJ-45	No of Ports	50
IDC cable size	22 to 26 AWG, Solid or stranded Cables	Metal Frame	Galvanized Steel
Colour	Black	Plug Holding Force	140N min
Storage temperature range	-20 to +80C	Temperature operating range	-40 to +60C
Dielectric strength	1000 VDC (Contact/Contact), 1500 VDC (Contact/Ground)	Connector Module Holder	Flame retardant plastic bileflen, UL 94 V-0

ORDERING INFORMATION

FVPP3U50F

Voice Patch Panel, Cat3, 50 Port, 1RU, Straight, Black